

LEIPA ultra **SQUARE**® silk

SPEZIFIKATION / SPECIFICATION / FICHE TECHNIQUE

| Flächengewicht | Weißgrad OS | Opazität | Glanz | Dicke* |
|-----------------------|----------------------------|--------------------|--------------------|------------------------|
| g/m ² | % | % | % | µm |
| substance grammage | brightness TS blancheur | opacity opacité | gloss brillance | thickness épaisseur |
| ISO 536 | ISO 2470 | DIN 53146 | ISO 8254-1 | EN 20534 |
| 60 ¹ | 82 | ≥ 92 | 20 | 66 |
| 65 ¹ | 84 | ≥ 92 | 20 | 72 |
| 70 | 84 | ≥ 92 | 20 | 77 |
| 80 | 84 | ≥ 94 | 20 | 88 |
| 90 | 84 | ≥ 94 | 20 | 99 |
| | | | | |
| | | | | |
| | | | | |

¹ auf Anfrage / on demand / sur demande

* Richtwert / observed value / valeur cible

Toleranzen / tolerances / tolérances

| | | | | |
|-------|-------|---|-----|---|
| ± 4 % | ± 2,5 | - | ± 2 | - |
|-------|-------|---|-----|---|

gültig ab / valid from / valable à partir du: 01.01.2018
 Link / link / lien: www.leipa.de/de/ko_produktbereiche



www.blauer-engel.de/uz72